

电气安装线缆

RVV



CCC A111033 60 浙江兆龙互连科技股份有限公司 227 IEC 52(RVV) 2X0.5mm² 300/300V ****m

产品应用
此产品适用于电气设备控制连接。适用于机床设备、成套设备安装，为固定安装铺设或偶尔移动。



技术参数

- 温度范围
60227 IEC 52 (RVV) -15℃ ~70℃
60227 IEC 53 (RVV) -15℃ ~70℃
60227 IEC 56 (RVV-90) -15℃ ~90℃
60227 IEC 57 (RVV-90) -15℃ ~90℃
- 测试电压
2000/5min (AC)
- 绝缘电阻 (70℃)
(见下表)
- 额定电压
60227 IEC 52 (RVV) 300/300V
60227 IEC 53 (RVV) 300/500V
60227 IEC 56 (RVV-90) 300/300V
60227 IEC 57 (RVV-90) 300/500V
- 最小弯曲半径
固定应用 :6D (D= 电缆直径)
偶尔移动: 15D (D= 电缆直径)
- 参考标准
GB/T5023.5,IEC60227-5

电缆结构

导体: 精细裸铜绞合导体, 符合 IEC 60228/VDE 0295 5 类导体标准
绝缘: PVC
绝缘颜色: 符合 GB/T5023.1
护套: PVC
颜色: 黑色

特点

通过中国国家强制性产品认证
阻燃满足 IEC60332-1 要求
具有很好的柔韧性
高质量, 经久耐用

产品编码	产品规格 (mm²)	标称外径 (mm)	铜重约 (kg/km)	电缆重量约 (kg/km)	绝缘电阻 (MΩ.km)
60227 IEC 52(RVV) 300/300V					
ZL5502057	2x0.50	5.1	9.4	35.9	0.012
ZL5502058	2x0.75	5.5	14.1	43.4	0.010
ZL5502096	3x0.50	5.4	14.1	47.8	0.012
ZL5502097	3x0.75	5.8	21.2	58.4	0.010
60227 IEC 53(RVV) 300/500V					
ZL5502098	2x0.75	6.2	13.7	48.1	0.011
ZL5502035	2x1.0	6.6	18.8	56.2	0.010
ZL5502060	2x1.5	7.2	27.5	72.9	0.010
ZL5502061	2x2.5	9.2	45.0	112.7	0.009
ZL5502099	3x0.75	6.6	21.2	62.1	0.011
ZL5502100	3x1.0	7.0	28.2	72.5	0.010
ZL5502101	3x1.5	8.3	41.3	104.0	0.010
ZL5502034	3x2.5	10.0	67.5	153.4	0.009
ZL5502102	4x0.75	7.2	28.2	76.5	0.011

电气安装线缆

产品编码	产品规格 (mm²)	标称外径 (mm)	铜重约 (kg/km)	电缆重量约 (kg/km)	绝缘电阻 (MΩ.km)
ZL5502062	4x1.0	7.8	37.6	94.1	0.010
ZL5502103	4x1.5	9.2	55.1	128.9	0.010
ZL5502104	4x2.5	10.9	90.0	190.3	0.009
ZL5502105	5x0.75	8.1	35.3	93.4	0.011
ZL5502106	5x1.0	8.6	47.0	111.1	0.010
ZL5502107	5x1.5	10.2	68.9	158.5	0.010
ZL5502108	5x2.5	11.2	112.5	233.8	0.009
60227 IEC 56(RVV) 300/300V					
ZL5502109	2x0.50	5.0	9.1	34.7	0.012
ZL5502110	2x0.75	5.5	13.7	42.0	0.010
ZL5502111	3x0.50	5.3	13.7	46.2	0.012
ZL5502112	3x0.75	5.8	20.5	56.5	0.010
60227 IEC 57(RVV) 300/500V					
ZL5502113	2x0.75	6.3	13.7	48.8	0.011
ZL5502114	2x1.0	6.6	18.3	55.5	0.010
ZL5502115	2x1.5	7.5	26.7	72.4	0.010
ZL5502116	2x2.5	9.2	43.7	109.5	0.009
ZL5502117	3x0.75	6.6	20.5	61.9	0.011
ZL5502118	3x1.0	7.0	27.4	72.0	0.010
ZL5502119	3x1.5	8.2	40.1	100.9	0.010
ZL5502120	3x2.5	10.0	65.5	151.4	0.009
ZL5502121	4x0.75	7.2	27.4	76.1	0.011
ZL5502122	4x1.0	7.8	36.5	93.0	0.010
ZL5502123	4x1.5	9.2	53.5	127.8	0.010
ZL5502124	4x2.5	10.9	87.3	187.7	0.009
ZL5502125	5x0.75	8.0	33.6	91.7	0.011
ZL5502126	5x1.0	8.6	45.6	109.7	0.010
ZL5502127	5x1.5	10.2	66.8	156.4	0.010
ZL5502128	5x2.5	12.2	109.2	230.6	0.009